

GENERAL SERIES BATTERY

6FM280/12Volt 280Ah

General Series VRLA batteries are designed with AGM(Absorbent Glass Mat) technology, High performance plates and electrolyte to give extra power output for common power backup system. General Series Batteries are the general purpose batteries with 10 years floating design life at 25°C.

APPLICATION

- ☆ Emergency Power System
- ☆ Communication equipment
- ☆ Telecommunication systems
- ☆ Uninterruptible power supplies
- ☆ Electric toy car and wheelchairs, etc
- ☆ Power tools
- ☆ Alarm system
- ☆ Marine equipment
- ☆ Medical equipment
- ☆ Fire and Security System

GENERAL FEATURES

- ☆ Heavy Duty Grid
- ☆ Mechanized assembly
- ☆ Non-spillable construction
- ☆ High Reliability and Stability
- ☆ Sealed and Maintenance-free
- ☆ Long Life and low self-discharge design

CONSTRUCTION


- ☆ Container: ABS(UL94-HB) / Flame Retardant ABS (UL94-V0)
- ☆ Negative: Lead
- ☆ Electrolyte: Sulfuric acid
- ☆ Safety Valve: EPDR
- ☆ Positive: Lead dioxide
- ☆ Separator: Fiber glass
- ☆ Terminal: Copper

SPECIFICATION

Battery Model	Nominal Voltage	12V			
	Rated capacity (10Hour rate)	280Ah			
	Cells Per battery	6			
Dimension	Length	Width	Height	Total Height	
	520mm	268mm	220mm	228mm	
Approx Weight	71.00Kg				
Internal Resistance	Full charged at 25°C(77°F): Approx 2.70mΩ				
Max.discharge current	2240A(5s)				
Floating design life @ 25°C (77°F)	10 years				
Capacity @ 25°C (77°F)	10Hour rate(28.0A/10.8V)	5Hour rate(47.60A/10.5V)	3Hour rate(70.0A/10.5V)	1Hour rate(154.0A/10.5V)	
	280Ah	238Ah	210Ah	154Ah	
Capacity affected by Temp(10 HR)	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C(5°F)	
	102%	100%	85%	65%	
Self Discharge @ 25°C (77°F)	After 3 months storage		After 6 months storage		After 12 months storage
	93%		84%		65%
Charge method @ 25°C (77°F)	Cycle Use	14.70-14.90V (Max. charge current: 75.00A)			
	Float Use	13.60-13.80V			

OUTER DIMENSION (mm)

TERMINAL TYPE (mm)




CONSTANT CURRENT(AMP) AND CONSTANT POWER(WATT) DISCHARGE TABLE AT 25°C (77°F)


F.V / TIME	5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h	
9.60V	A	1008.00	616.00	490.00	322.00	169.40	98.00	72.80	58.80	49.12	32.43	30.80	15.96
	W	10684.80	6541.92	5243.00	3477.60	1846.46	1068.20	800.80	646.80	540.28	360.01	341.88	179.55
10.20V	A	924.00	590.80	450.33	305.67	168.00	94.03	71.40	56.00	48.18	31.92	29.40	15.68
	W	10071.60	6557.88	5021.22	3438.75	1890.00	1062.58	806.82	635.60	546.88	362.29	333.69	177.97
10.50V	A	856.92	564.65	420.00	296.33	154.00	92.17	70.00	53.20	47.60	31.50	28.84	15.48
	W	9426.08	6352.29	4746.00	3378.19	1755.60	1055.31	801.50	611.80	547.40	362.25	331.66	178.07
10.80V	A	780.27	559.78	392.00	282.80	159.60	89.83	68.60	52.27	45.50	30.68	28.00	15.29
	W	8582.93	6381.45	4488.40	3266.34	1843.38	1037.57	795.76	608.91	530.08	357.46	326.20	178.11
11.10V	A	674.80	532.00	364.00	263.20	154.00	87.50	65.80	51.33	43.52	29.87	27.30	15.12
	W	7625.24	6144.60	4222.40	3079.44	1801.80	1023.75	773.15	605.73	513.50	352.43	322.14	178.42

6FM280/12Volt 280Ah


Discharge characteristic Curve




Charge Characteristic Curve For Standby Use




Cycle service life in relation to depth of discharge




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity



Storage Characteristics



Effect Of emperature On Long Term Life



Charge Characteristic Curve For Standby Use

